



Conventional Zone Monitor Unit - 1 Zone

KAL410

Allows the connection of one conventional zone to the analogue fire system loop. This zone is constantly monitored. Up to 20 conventional devices may be connected to this zone.

Specifications

Supply voltage	22-38 VDC
Current consumption	
Quiescent @ 24 V	90 A
Quiescent @ 35 V	105 A
Alarm	< 3 mA
Aux. supply (24 VDC) quiescent	200 A + equip
Aux. supply (24 VDC) alarm	< 85 mA
End-of-line resistor	4.7 kohm
Relay contact rating	NA
Environmental	
Storage temperature	-10 °C to +50°C
Operating temperature	-10 °C to +70°C
Relative humidity	95 % (non condensing)
Dimensions (L x W x H)	117 x 80 x 44 mm



Ordering Information

KAL410            Conventional Zone Monitor Unit - 1 Zone

- Easy numeric addressing
- Continuous supervision of the conventional zones
- Surface mount
- Local alarm indication
- Externally powered
- Aesthetically pleasing
- Part of family of I/O modules consisting of:
  - Conventional Zone Monitors
  - Digital Input Modules
  - Extinguishing Control Modules
  - Isolator Modules
  - Manual Call Points
  - Output Units
  - Retention Units
  - Supervised Output Units for sounder control

Distribuição: Segurança Industrial Equipamentos  
Fone/Fax: (41) 4063-9687  
cml@segind.com.br - segind@hotmail.com  
www.segind.com.br