



Conventional Zone Monitor Unit - 4 Zones

KAL414C

Allows the connection of four conventional zones to the analogue fire system loop. These zones are constantly monitored. Up to 20 conventional devices may be connected to any zone.

Specifications

Supply voltage	22-38 VDC
Current consumption	
Quiescent @ 24 V	110 A
Quiescent @ 35 V	135 A
Alarm	< 5 mA
Aux. Supply (24V DC) Quiescent	200 A + equip
Aux. Supply (24V DC) Alarm	< 360 mA
End-of-line resistor	4.7 kOhm
Relay contact rating	NA
Environmental	
Storage temperature	-10 to +50°C
Operating temperature	-10 to +70°C
Relative humidity (non-condensing)	0-95 %
Dimensions (l x w x h)	163 x 107 x 36 mm

Ordering Information

KAL414C            Conventional Zone Monitor Unit - 4 Zones



- Easy numeric addressing
- Continuous supervision of the conventional zones
- Surface mount
- Local alarm indication
- Externally powered
- Aesthetically pleasing
- Part of a family of I/O modules consisting of:
  - - Conventional Zone Monitors
  - - Digital Input Modules
  - - Extinguishing Control Modules
  - - Isolator Modules
  - - Manual Call Points
  - - Output Units
  - - Retention Units
  - - Supervised Output Units for sounder control