



Equally at home in prestigious installations and commercial interiors, Vistral is an ultra-low profile luminaire with a stylish design, allowing it to blend unobtrusively into any environment. The luminaire has a maximum depth of only 50mm and appears even slimmer thanks to an elegantly curved upper gallery, which also incorporates the efficient clear fresnel lens. The excellent flashing developed by this wide lens also permits Vistral to be deployed as an attractive exit sign, using the optional legend kit.

- BSI kitemarked for peace of mind
- ICEL registered with verified light performance
- Attractive, curved, low profile design suits most environments
- Stylish exit sign using legend kit, complies to EN 1838
- EasiCheck, Intellem and CeaGuard self-testing options
- Available in self-contained, AC/DC and AC mains slave versions
- Supplied with lamp

### Lamp Options

- 8W T5 fluorescent, 3500°K - G5 cap


### Materials

- Upper/lower gallery - polycarbonate and ABS
- Lens - clear polycarbonate
- Batteries (self-contained versions) - NiCd

### Installation Notes

- Suitable for ceiling or wall mounting
- Lower gallery fixed direct, via keyhole slots
- BESA entry on rear. Cable entries on side and end
- Upper gallery and lens have snap fix retention
- Supplied complete with 1 x 8W lamp

### Dimensions



### Catalogue Numbers

System Mode	Cat No	Weight (kg)
Non Maintained 3Hr	VSN	1.2
Non Maintained 3Hr Self-test	VSNIS	1.2
Non Maintained 3Hr EasiCheck	VSNEC	1.2
Non Maintained 3Hr EasiCheck 2	VSNEC2	1.2
Maintained 3Hr	VSM	1.4
Maintained 3Hr Self-test	VSMIS	1.4
Maintained 3Hr EasiCheck	VSMEC	1.4
Maintained 3Hr EasiCheck 2	VSMEC2	1.4
230V Ceaguard Slave	VS230CG	0.95
230V AC Mains Slave	VS8S230	0.95
230V AC Mains Slave EasiCheck	VS8S230EC	0.95
50V AC/DC Central System Slave	VS50	0.95
110V AC/DC Central System Slave	VS110	0.95

Legend Panel	Cat No	Weight (kg)
European Format self-adhesive legend kit	LEXSAVS	0.05

### Options

- Maintained and Non-maintained operation, 3 hour duration
- Intellem self-test. Technology detailed on page 309
- EasiCheck addressable testing. System detailed on page 304
- Central system slave versions
- CeaGuard testing versions

### Specification

Self contained - To specify state: BSI Kitemarked and ICEL registered, 50mm deep ultra-low, curved profile decorative self contained emergency luminaire, with snap fix high quality fresnel lens and upper gallery, in white finish, as Menvier Vistral range, part no.

Self-test/Slave - To specify state: Intelligent self-testing/Central system slave compatible, 50mm deep ultra-low curved profile decorative emergency luminaire, with snap fix high quality fresnel lens and upper gallery, in white finish, as Menvier Vistral range, part no.

### Photometric Data

Mode	Mounting height (m)	Escape route 2m wide 1 lux min					Open (anti-panic) area 0.5 lux min			
		Lux level directly under								
Self-contained										
NM	2.5	2.70	2.4	5.8	5.4	1.9	2.0	6.3	6.2	1.9
	4.0	1.06	1.6	7.2	5.1	0.6	2.5	7.4	7.0	1.7
	6.0	0.47	-	-	-	-	-	8.8	7.4	-
M	2.5	2.16	2.3	5.6	5.0	1.7	2.0	5.9	5.7	1.7
	4.0	0.90	-	6.8	4.4	-	2.3	7.0	6.7	1.5
	6.0	0.40	-	-	-	-	-	8.5	7.0	-
Slave										
AC/DC	2.5	4.89	2.9	6.8	6.8	2.6	2.3	7.5	7.2	2.3
	4.0	1.91	3.5	8.6	7.4	2.3	3.0	8.9	8.9	2.5
	6.0	0.85	-	-	-	-	3.5	10.0	9.8	2.1
AC/AC	2.5	6.7	3.1	7.8	7.8	3.0	2.7	8.4	7.7	2.0
	4.0	2.6	3.9	9.0	8.4	2.9	3.2	9.8	9.8	2.1
	6.0	1.1	3.1	11.2	7.6	1.4	3.9	11.2	11.2	1.9